

Technical data sheet

Fundo sealing set

- System designed for wedi Fundo



General product description

Bucket set, consisting of a 2-component sealant, wedi Tools sealing tape and wedi Tools inner sealing corners for flexible joint sealing.

Applications

For sealing wedi Fundo joints and wedi building boards in wet areas.

Product properties


- Waterproof and frost-resistant, for universal indoor and outdoor use
- Ageing-resistant, unaffected by environmental influences
- Crack-bridging, provides good protection against subsequent surface cracking

Processing

Put the liquid component into the bucket supplied and mix in a machine with the lump-free powder component until a homogeneous processing consistency is achieved. Using a trowel, apply to the whole surface of the joints as a scratch layer. Use wedi sealing tape in the first layer and cover fully with the second layer.



* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant A+ (très faibles émissions) à C (fortes émissions).



Technical properties of sealant

Powder component	Special cement mortar with selected additives
Liquid component	Modified acrylate dispersion
Maturing time	approx. 3 minutes
Processing time	approx. 45 minutes (at +20°C/50% rel. humidity) Higher temperatures and humidity will reduce the specified times, lower temperatures will extend them.
Processing temperature	+5°C to +25°C
Rain resistance	(at +20°C and 50% relative humidity) Can be walked on after approx. 6 hours Ceramic covers can be applied after approx. 12 hours Can be exposed to contact with water after approx. 3 days

For technical values of the sealing tape, see wedi Tools sealing tape/sealing corners data sheet.

Consumption

Sufficient for approx. 10 m of joint seals.

Packing

- Powder component: 2.4 kg
- Liquid component: 1.2 kg
- Sealing tape: 10 m
- Sealing corners inner: x 2
- Packaging: bucket

Storage

Store dry and frost-free, closed in original container; can be stored for 12 months.

Safety notice



The product is rated and marked in accordance with CLP regulations.
H315 causes skin irritation
H318 causes serious eye damage
H335 may cause respiratory irritation

Any information on processing and application options of wedi products, technical recommendations, consulting or any other information by our employees (advice on the use of the product) are provided to the best of our knowledge, however, without obligation and excluding any liability. Our clients and their customers are responsible for carrying out their own tests to ensure suitability of the products for the intended applications and purposes.